NSN 4820-00-229-2998

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-229-2998

Pipe Size Accommodated:

0.250 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.0 cubic feet per minute

Maximum Operating Temp:

125.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Features Provided:

Valve stem lock shield and pressure tight outlet side

Adjustable Pressure Range:

+55.0/+200.0 pounds per square inch

Maximum Operating Pressure:

155.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Opening Pressure Setting:

155.0 pounds per square inch

Material:

Silicon flow control device

Media For Which Designed:

Air single response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

NSN 4820-00-229-2998

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

