NSN 4820-00-229-9550

Globe Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-229-9550

Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
850.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
6.125 inches 1st end
Face To Face Distance:
9.000 inches
Thickness:
0.750 inches 1st end
Bolt Hole Diameter:
1.000 inches 1st end
Bolt Circle Diameter:
4.500 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
2.875 inches 1st end
Material:
Steel stem
Media For Which Designed:
Steam single response
Style Designator:
Straight through flanged ends

NSN 4820-00-229-9550

Globe Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0