## NSN 4820-00-230-2143

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-230-2143
Body Material:
Aluminum alloy, qq-a-225/6, alloy 2024, t4
Outside Surface Treatment:
Anodized, mil-a-8625, type 1
Body Style:
Angle
First End Connection Type:
Threaded internal boss
First End Style Designator:
Gasket seal
First End Thread Size And Series/type Designator:
7/16-20 unf
First End Thread Class:
2b
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
Third End Relationship With Preceding Ends:
Identical with first end
Seat Material:
Plastic, polyamide mil-m-20693
Flow Control Device:
Poppet
Flow Control Device Material:
Steel, federal standard 66, aisi 302/sae 30302
End Connection Quantity:

3

**Regulation Type:** 

Automatic double stage

Valve Loading Method:

Spring

**Maximum Inlet Pressure Rating:** 

3000.0 pounds per square inch

**Outlet Pressure Setting:** 

590.0 pounds per square inch

**Outlet Pressure Accuracy Rating:** 

Not rated

Filter:

Not included

**Tempurature Rating:** 

Between -54.0 degrees celsius and 71.0 degrees celsius

## NSN 4820-00-230-2143

Fluid Pressure Regulating Valve - Page 2 of 2



$\sim$				
•	no	ıŦ	ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A21100