## NSN 4820-00-230-2150

**Body Material:** 

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-230-2150

Aluminum alloy, qq-a-225/6, alloy 2024, t4 **Outside Surface Treatment:** Anodized, mil-a-8625, type 1 **Body Style:** Angle **First End Connection Type:** Threaded internal boss First End Style Designator: Gasket seal First End Thread Size And Series/type Designator: 7/16-20 unf First End Thread Class: 2b **First End Thread Direction:** Right-hand Second End Relationship With First End: Identical Third End Relationship With Preceding Ends: Identical with first end **Seat Material:** Polyamide mil-m-20693 mfr 81349 **Center To Center Distance:** 2.375 inches **Flow Control Device: Poppet** Flow Control Device Material: Steel, federal standard 66, aisi 302/sae 30302 **End Connection Quantity:** 3 **Outlet Pressure Range:** +1280.0 to 1350.0 pounds per square inch **Regulation Type:** Automatic double stage **Valve Loading Method:** Spring **Maximum Inlet Pressure Rating:** 3000.0 pounds per square inch **Outlet Pressure Accuracy Rating:** Not rated

Filter:

Not included

## NSN 4820-00-230-2150

Fluid Pressure Regulating Valve - Page 2 of 2



Tempurature Rating:	T	em	pur	atur	e F	≀atiı	ng:
---------------------	---	----	-----	------	-----	-------	-----

Between -54.0 degrees celsius and 71.0 degrees celsius

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A21100