

View Online at <https://aerobasegroup.com/nsn/4820-00-231-2308>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 2nd end

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Features Provided:

Valve stem lock shield and bonnet packing

Valve Size:

3.000 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Opening Pressure Setting:

500.0 pounds per square inch

Outside Diameter:

8.250 inches 1st end

Thickness:

1.250 inches 1st end

First Connection Face To Centerline Distance:

8.688 inches

Bolt Hole Diameter:

0.875 inches 2nd end

Second Connection Face To Centerline Distance:

8.188 inches

Bolt Circle Diameter:

9.500 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

8.500 inches 2nd end

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by flanged connection sizes

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0