Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-231-5627

Bronze Bronze Bronze Bronze Bronze Bronze Straight thu Media For Which Designed: Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 20.0.0 degrees fahrenheit Special Fe	Body Material:
Body Style: Straight thu Media For Which Designed: Vater First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximun Inlet Pressure Rating: 20.0 pounds per square inch Filter: Included Tempurature Rating: 20.0. degrees fahrenheit Spcial Features: Playot, polytetrafluoroethylene/ffe	
Straight thuMedia For Which Designed:VaterFirst End Connection Type:Threaded internal pipeFirst End Style Designator:PlainFirst End Thread Size And Series/type Designator:3/4-14 nptfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:DiaphragmEnd Connection Quantity:2Renewable Seat Ring Type:Any acceptableRegulation Type:Single seatValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:20.0 pounds per square inchFilter:IncludedTempurature Rating:20.0 degrees fahrenheitSpecial Features:Plackic, polytetrafluoroethylene/tfe	
Media For Which Designed:WaterFirst End Connection Type:Threaded internal pipeFirst End Style Designator:PlainFirst End Thread Size And Series/type Designator:3/4-14 nptfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:DiaphragmEnd Connection Quantity:2Regulation Type:Any acceptableRegulation Type:Single seatValve Stem Design:Single seatPairagmEnder Actuation Method:SpringRemote Actuation Method:DiaphragmMaximum Intel Pressure Rating:20.0 pounds per square inchFilter:IncludedTempurature Rating:20.0 degrees fahrenheitSpecial Features:212223242424252526272829200 </td <td></td>	
Water First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Regulation Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Mature Intel Pressure Rating: 20.0 pounds per square inch Filter: Included Temperature Rating: 20.0 degrees fahrenheit Spcial Features: Plastic, polytetrafluoroethylene/ffe	-
First End Connection Type: Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	-
Threaded internal pipe First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
First End Style Designator: Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Spring Remote Actuation Method: Diaphragm Maximum Intel Pressure Rating: 20.0 pounds per square inch Filte: Included Tempurature Rating: 20.0.1 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
Plain First End Thread Size And Series/type Designator: 3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 20.0 pounds per square inch Filte: Included Tempurature Rating: 20.0.1 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
First End Thread Size And Series/type Designator:3/4-14 nptfFirst End Thread Direction:Right-handSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:DiaphragmEnd Connection Quantity:2Renewable Seat Ring Type:Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedZenourating:200.0 degrees fahrenheit200.0 degrees fahrenheit200.0 degrees fahrenheit200.0 polytetrafluoroethylene/tfe	
3/4-14 nptf First End Thread Direction: Right-hand Second End Relationship With First End: Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
First End Thread Direction:Right-handSecond End Relationship With First End:IdenticalSeat Material:Nickel copper alloyFlow Control Device:DiaphragmEnd Connection Quantity:2Renewable Seat Ring Type:Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:DiaphragmMaximum Inlet Pressure Rating:20.0 pounds per square inchFilter:IncludedZou.0 degrees fahrenheitSpreial Features:Plastic, polytetrafluoroethylene/tfe	
Right-handSecond End Relationship With First End:IdenticalJenticalSeat Material:Nickel copper alloyFlow Control Device:DiaphragmEnd Connection Quantity:2Renewable Seat Ring Type:Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatSpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedZou.0 degrees fahrenheitSpreial Features:Poscial Features:Poscial Features:Poscia, polytetrafluoroethylene/ffe	-
Second End Relationship With First End: Identical Beat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Filter: Included Diaphragm: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/ffe	
Identical Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Nanual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/ffe	-
Seat Material: Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	-
Nickel copper alloy Flow Control Device: Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
Flow Control Device:DiaphragmEnd Connection Quantity:2Renewable Seat Ring Type:Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedZenpurature Rating:200.0 degrees fahrenheitSpecial Features:Plastic, polytetrafluoroethylene/tfe	
Diaphragm End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
End Connection Quantity: 2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	
2 Renewable Seat Ring Type: Any acceptable Regulation Type: Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Filter: Jonudeg State Stat	
Renewable Seat Ring Type:Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedZon.0 degrees fahrenheitSpring:Plastic, polytetrafluoroethylene/tfe	End Connection Quantity:
Any acceptableRegulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedTempurature Rating:200.0 degrees fahrenheitSpecial Features:Plastic, polytetrafluoroethylene/tfe	
Regulation Type:Manual single stageValve Stem Design:Single seatValve Loading Method:SpringRemote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedTempurature Rating:200.0 degrees fahrenheitSpecial Features:Plastic, polytetrafluoroethylene/tfe	Renewable Seat Ring Type:
Manual single stage Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Any acceptable
Valve Stem Design: Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Regulation Type:
Single seat Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Manual single stage
Valve Loading Method: Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Valve Stem Design:
Spring Remote Actuation Method: Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Single seat
Remote Actuation Method:DiaphragmMaximum Inlet Pressure Rating:200.0 pounds per square inchFilter:IncludedTempurature Rating:200.0 degrees fahrenheitSpecial Features:Plastic, polytetrafluoroethylene/tfe	Valve Loading Method:
Diaphragm Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Spring
Maximum Inlet Pressure Rating: 200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Remote Actuation Method:
200.0 pounds per square inch Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Diaphragm
Filter: Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Maximum Inlet Pressure Rating:
Included Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	200.0 pounds per square inch
Tempurature Rating: 200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Filter:
200.0 degrees fahrenheit Special Features: Plastic, polytetrafluoroethylene/tfe	Included
Special Features: Plastic, polytetrafluoroethylene/tfe	Tempurature Rating:
Plastic, polytetrafluoroethylene/tfe	200.0 degrees fahrenheit
	Special Features:
Shelf Life:	Plastic, polytetrafluoroethylene/tfe
	Shelf Life:
N/a	N/a

Fluid Pressure Regulating Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100