## NSN 4820-00-234-7103

Check Valve - Page 1 of 2

Thread Class: 3a 1st end

Poppet

Spring

Thread Direction:
Right-hand 1st end
Flow Control Device:

**Disk Loading Method:** 



View Online at https://aerobasegroup.com/nsn/4820-00-234-7103

Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
1.062 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.750 inches 1st end
Material:
Steel comp 316 seat
Material Specification:
Qq-s-763 federal specification single material response seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Passivate
Surface Treatment Specification:
Esf59-2, fscm 92003 mfr ref single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf 2nd end

## NSN 4820-00-234-7103

Check Valve - Page 2 of 2



	<b>L</b> -	11		ife	_
3	ne	п	_	пe	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0