NSN 4820-00-241-0634

Check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-241-0634

g p
Thread Class:
3a all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
180.0 degrees fahrenheit 2nd response
End Application:
Helicopter, advance attack, ah-1w; helicopter, cobra/attack, ah-1j
Connection Style:
Flared (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
14 1st end
Maximum Operating Pressure:
600.0 pounds per square inch single response
Thread Size:
0.875 inches all ends
Seat Angle:
37.0 degrees 1st end
Criticality Code Justification:
Feat
Opening Pressure Setting:
18.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.625 inches 1st end
Special Features:
Weapon system essential
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6 federal specification single material response seat

Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

NSN 4820-00-241-0634

Check Valve - Page 2 of 2



Style Des	ignator:
-----------	----------

Straight thru

Thread Series Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0