## NSN 4820-00-241-0734

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-241-0734

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
5.0 gallons per minute
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Mounting Facility:
Bulkhead
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
16 1st end
Adjustable Pressure Range:
+10.0/+150.0 pounds per square inch
Maximum Operating Pressure:
1000.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Material:
Aluminum alloy seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a

## NSN 4820-00-241-0734

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0