## NSN 4820-00-243-2474

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-243-2474

Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Threaded
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
371.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
5.250 inches 1st end
Face To Face Distance:
8.500 inches
Thickness:
0.812 inches 1st end
Bolt Hole Diameter:
0.625 inches 1st end
Bolt Circle Diameter:
3.875 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
0.625 inches 1st end
Material:
Steel stem
Material Specification:
Astm a216, gr wcb assn standard single material response body

## NSN 4820-00-243-2474

Globe Valve - Page 2 of 2



N	ledia	For	Whi	ich	Des	ian	ed:
٧	ieuia	ги	VVII	ICH	Des	uun	eu.

Fuel/oil, hydrocarbon single response

**Style Designator:** 

Straight through flanged ends

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0