

View Online at <https://aerobasegroup.com/nsn/4820-00-243-2474>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

371.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

5.250 inches 1st end

Face To Face Distance:

8.500 inches

Thickness:

0.812 inches 1st end

Bolt Hole Diameter:

0.625 inches 1st end

Bolt Circle Diameter:

3.875 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

0.625 inches 1st end

Material:

Steel stem

Material Specification:

Astm a216, gr wcb assn standard single material response body

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Straight through flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0