NSN 4820-00-243-6703

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-243-6703

Pipe Size Accommodated:
0.500 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+136.0/+150.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Criticality Code Justification:
Zzzy
Opening Pressure Setting:
136.0 pounds per square inch
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle
Reference Number Differentiating Characteristics:
Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli

NSN 4820-00-243-6703

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0