NSN 4820-00-246-3106

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-246-3106

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
25.6 cubic feet per minute
Connection Style:
Plain (pipe) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Maximum Operating Pressure:
385.0 pounds per square inch single response
Thread Size:
0.875 inches 1st end
Seat Angle:
45.0 degrees 1st end
Opening Pressure Setting:
385.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.625 inches 1st end
Material:
Copper alloy and rubber synthetic flow control device
Media For Which Designed:
Refrigerant 12 1st response
Style Designator:
Err-090
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-246-3106

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0