

View Online at <https://aerobasegroup.com/nsn/4820-00-247-8693>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

55.0 gallons per minute

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

150.0 degrees fahrenheit single response

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Mounting Facility:**

Bracket

**Features Provided:**

Valve stem lock shield and pressure tight outlet side

**Adjustable Pressure Range:**

+42.0/+56.0 pounds per square inch

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Outside Diameter:**

4.625 inches all ends

**Thickness:**

0.625 inches all ends

**Bolt Hole Diameter:**

0.625 inches all ends

**Bolt Circle Diameter:**

3.500 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Steel stem

**Media For Which Designed:**

Water, salt single response

**Style Designator:**

Angle

**Specification Or Standard:**

A grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0