## NSN 4820-00-247-9183

Safety Relief Valve - Page 1 of 2



Saisty Relief Valve Tage For 2
View Online at https://aerobasegroup.com/nsn/4820-00-247-9183
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 2nd end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+400.0/+600.0 pounds per square inch
Maximum Operating Pressure:
2500.0 pounds per square inch single response
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
550.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 2nd end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response

Media For Which Designed:

Hydrogen 2nd response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 1 military specification single treatment response

Style Designator:

Straight through note: to be used for valve bodies of separable sections.

## NSN 4820-00-247-9183

Safety Relief Valve - Page 2 of 2



Thread Series Designator:	
Unjf 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A046b0	

Mil-std (military Standard):

Mil-a-8625 spec.