

View Online at <https://aerobasegroup.com/nsn/4820-00-248-6398>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

16300.0 pounds per hour

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

4 2nd end

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Features Provided:

Pressure tight outlet side

Valve Size:

1.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Opening Pressure Setting:

473.0 pounds per square inch

Outside Diameter:

7.500 inches 2nd end

Thickness:

1.500 inches 1st end

First Connection Face To Centerline Distance:

5.750 inches

Bolt Hole Diameter:

0.875 inches 1st end

Second Connection Face To Centerline Distance:

7.000 inches

Bolt Circle Diameter:

6.000 inches 2nd end

Flange Face Design:

Raised straight 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

5.000 inches 2nd end

Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by adjustable pressure range

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0