NSN 4820-00-252-4830



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-252-4830 Flow Control Device: Disk **Bonnet Type:** Exposed spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 59900.0 pounds per hour **Renewable Seat Ring Type:** Threaded **Bolt Hole Quantity:** 9 2nd end **Valve Operation Method:** Automatic or manual Flange Shape: Round with holes 2nd end **Connection Type:** Flange 1st end **Adjustable Pressure Range:** +1246.0/+1379.0 pounds per square inch **Opening Pressure Setting:** 1365.0 pounds per square inch **Outside Diameter:** 9.625 inches 1st end **Bolt Hole Diameter:**

1.062 inches 1st end

Bolt Circle Diameter:
7.688 inches 2nd end

Flange Face Design:
Plain 2nd end

Style Designator:
Angle

Reference Number Differentiating Characteristics:
As differentiated by the valve discharge flow rate requirement

Shelf Life:
N/a

Unit Of Measure:
--
Demilitarization:

No

NSN 4820-00-252-4830

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0