NSN 4820-00-252-4852

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-252-4852

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 2nd end
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Features Provided:
Pressure tight outlet side
Valve Size:
1.500 inches
Opening Pressure Setting:
675.0 pounds per square inch
Outside Diameter:
7.500 inches 1st end
Thickness:
0.875 inches 2nd end
First Connection Face To Centerline Distance:
5.718 inches
Bolt Hole Diameter:
0.875 inches 2nd end
Second Connection Face To Centerline Distance:
6.938 inches
Bolt Circle Diameter:
6.000 inches 1st end
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:

5.000 inches 1st end

NSN 4820-00-252-4852

Safety Relief Valve - Page 2 of 2

A046b0



Material:
Stainless steel seat
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
As differentiated by the opening pressure setting requirement
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: