NSN 4820-00-254-5849

Calibrated Flow Valve - Page 1 of 2

Body Material: Aluminum alloy

Anodized

Outside Surface Treatment:



View Online at https://aerobasegroup.com/nsn/4820-00-254-5849

Body Style:
Angle
Stem Material:
Steel, corrosion resisting
Media For Which Designed:
Not specified
First End Connection Type:
Threaded internal tube
First End Style Designator:
Plain
First End Outside Diameter Tube Accommodated:
0.750 inches
First End Thread Size And Series/type Designator:
1-1/16-12 un
First End Thread Class:
3b
First End Thread Direction:
Right-hand
Second End Relationship With First End:
Identical
First End Seat Radius:
Any acceptable
Packing Material:
Rubber, buna-n
Flow Control Device:
Piston, spring loaded
Flow Control Device Material:
Steel, corrosion resisting
End Connection Quantity:
2
Valve Discharge Flow Rate:
Any acceptable
Mounting Facility:
Internal thread
Regulation Type:
Manual, double stage
Manual Control Method:
Knob

NSN 4820-00-254-5849

Calibrated Flow Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100