## NSN 4820-00-260-4226

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-260-4226

Pipe Size Accommodated:
0.375 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
20.0 cubic feet per minute
Maximum Operating Temp:
300.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
Power Drive Operating Pressure:
108.0 pounds per square inch
Maximum Operating Pressure:
225.0 pounds per square inch single response
Thread Size:
0.375 inches 1st end
Opening Pressure Setting:
200.0 pounds per square inch
Material:
Copper alloy
Media For Which Designed:
Air single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

## NSN 4820-00-260-4226

Safety Relief Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A046b0