## NSN 4820-00-262-6896

Cross Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-262-6896

Pipe Size Accommodated:

0.250 inches 1st end

**Thread Direction:** 

Right-hand 1st end

## Flow Control Device:

Disk

#### Bonnet Type:

Inside screw

#### **Bonnet Attachment Method:**

Union

## Renewable Seat Ring Type:

Threaded

## Maximum Operating Temp:

36.0 degrees fahrenheit single response

#### **Connection Style:**

Plain, optional en (pipe) 1st end

## Valve Operation Method:

Manual

## **Connection Type:**

Threaded internal pipe 1st end

## **Features Provided:**

Bonnet packing

## Thready Qty Per Inch (tpi):

18 1st end

## Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

#### **Thread Size:**

0.250 inches 1st end

#### Material:

Steel flow control device

#### **Material Specification:**

Qq-n-288, comp b federal specification single material response stem

## Media For Which Designed:

Water-oil-gas 2nd response

## Style Designator:

Cross

## **Test Data Document:**

81349-mil-v-1202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Npt 1st end

#### **Specification Or Standard:**

3 type and c style and 150 class

# NSN 4820-00-262-6896

Cross Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

