

View Online at <https://aerobasegroup.com/nsn/4820-00-262-6899>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

366.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

0.750 inches all ends

Material:

Steel flow control device

Material Specification:

Qq-n-288, compb federal specification single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Cross

Test Data Document:

81349-mil-v-1202 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Specification Or Standard:

3 type and c style and 150 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0