

View Online at <https://aerobasegroup.com/nsn/4820-00-262-7017>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Integral

**Renewable Seat Ring Type:**

Threaded

**Maximum Operating Temp:**

406.0 degrees fahrenheit 1st response

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Thread Size:**

0.500 inches all ends

**Material:**

Plastic polytetrafluoroethylene packing and asbestos packing

**Material Specification:**

Astm b62 assn standard single material response flow control device

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Angle

**Thread Series Designator:**

Npt all ends

**Specification Data:**

59646-mss sp-80 manufacturers standard

**Specification Or Standard:**

2 type and a class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0