

View Online at <https://aerobasegroup.com/nsn/4820-00-262-8744>

Flow Control Device:

Disk

Disk Loading Method:

Weight

Bolt Hole Quantity:

4 2nd end

Connection Style:

Plain (tube) 1st end

Width:

1.594 inches 2nd end

Length:

1.594 inches 2nd end

Valve Operation Method:

Automatic

Flange Shape:

Rectangular with holes 2nd end

Connection Type:

Unthreaded internal tube 1st end

Mounting Position:

Vertical

Maximum Operating Pressure:

400.0 pounds per square inch single response

Thickness:

0.250 inches 2nd end

Bolt Hole Diameter:

0.188 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.156 inches 2nd end

Center To Center Distance Between Bolt Holes Along Width:

1.156 inches 2nd end

Flange Face Design:

Plain 2nd end

Outside Diameter Tube Accommodated:

0.625 inches 1st end

Special Features:

0.609 in. Center hole in flange of inlet connection

Material:

Steel comp 303 flow control device

Material Specification:

Qq-s-764, type 303-canceled federal specification single material response flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Style Designator:

Straight thru

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.