## NSN 4820-00-269-2620

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-269-2620

| Pipe Size Accommodated:  |
|--|
| 0.125 inches 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Flow Control Device:   |
| Poppet   |
| Bonnet Type:   |
| Inside spring  |
| Bonnet Attachment Method:  |
| Integral   |
| Disk Loading Method:   |
| Spring   |
| Connection Style:  |
| Plain, optional en (pipe) 1st end                                |
| Valve Operation Method:  |
| Automatic  |
| Connection Type:   |
| Threaded internal pipe 1st end                                   |
| Thready Qty Per Inch (tpi):                                      |
| 27 1st end   |
| Adjustable Pressure Range:                                       |
| +320.0/+370.0 pounds per square inch                             |
| Thread Size:   |
| 0.125 inches 2nd end   |
| Material:  |
| Stainless steel seat   |
| Material Specification:  |
| Qq-a-367, t6 federal specification single material response body |
| Style Designator:  |
| Angle  |
| Thread Series Designator:  |
| Npt 1st end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A046b0   |