## NSN 4820-00-273-1025

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-273-1025

Thread Direction:
Right-hand 2nd end
Flow Control Device:
Poppet
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Bolt Hole Quantity:
3 1st end
Connection Style:
Plain, optional en (pipe) 2nd end
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 1st end
Connection Type:
Threaded internal pipe 2nd end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+0.0/+12.0 pounds per square inch
Maximum Operating Pressure:
100.0 pounds per square inch single response
Thread Size:
0.500 inches 2nd end
Outside Diameter:
3.562 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
2.437 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Angle

## NSN 4820-00-273-1025

Safety Relief Valve - Page 2 of 2



**Thread Series Designator:** 

Npt 2nd end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0