

View Online at <https://aerobasegroup.com/nsn/4820-00-273-8918>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

14 1st end

**Maximum Operating Temp:**

425.0 degrees fahrenheit single response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes 1st end

**Connection Type:**

Flange 1st end

**Features Provided:**

Bonnet packing

**Valve Size:**

8.000 inches

**Maximum Operating Pressure:**

100.0 pounds per square inch single response

**Outside Diameter:**

12.375 inches 1st end

**Thickness:**

0.675 inches 1st end

**First Connection Face To Centerline Distance:**

9.750 inches

**Bolt Hole Diameter:**

0.688 inches 1st end

**Second Connection Face To Centerline Distance:**

9.750 inches

**Bolt Circle Diameter:**

11.062 inches 1st end

**Flange Face Design:**

Plain 1st end

**Material:**

Nickel alloy flow control device

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Angle flanged ends

**Test Data Document:**

80064-5000s4824-1385541 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0