

View Online at <https://aerobasegroup.com/nsn/4820-00-274-7389>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

0.500 inches all ends

Material:

Rubber synthetic flow control device

Material Specification:

Astmcu0172 assn standard single material response bodyastmrcb000 assn standard single material response flow control deviceastmpcaw00 assn standard single material response packing and astmasa000 assn standard single material response packingastmcub000 assn standard single material response seatastmcu0697 assn standard single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight thru

Thread Series Designator:

Npt all ends

Specification Or Standard:

2 type and 1 style and b class and 1/2 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0