

View Online at <https://aerobasegroup.com/nsn/4820-00-274-7390>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Maximum Operating Temp:

366.0 degrees fahrenheit single response

End Application:

Grumman; a10 aircraft

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

14 1st end

Maximum Operating Pressure:

300.0 pounds per square inch 2nd response

Thread Size:

0.750 inches all ends

Special Features:

Renewable composition disc.

Material:

Silicon stem and copper alloy stem

Material Specification:

Astm d1457 assn standard single material response packing and astm d375 assn standard single material response packing

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight thru

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 59646 have indicated their part number contained asbestos prior to 1984; they continue to manufacturer the same part number without asbestos material after 1984

Thread Series Designator:

Npt all ends

Furnished Items And Quantity:

1 handwheel

Specification Or Standard:

1 type and b class and 1 end and 3/4 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0