

View Online at <https://aerobasegroup.com/nsn/4820-00-274-7390>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Maximum Operating Temp:**

366.0 degrees fahrenheit single response

**End Application:**

Grumman; a10 aircraft

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Thready Qty Per Inch (tpi):**

14 1st end

**Maximum Operating Pressure:**

300.0 pounds per square inch 2nd response

**Thread Size:**

0.750 inches all ends

**Special Features:**

Renewable composition disc.

**Material:**

Silicon stem and copper alloy stem

**Material Specification:**

Astm d1457 assn standard single material response packing and astm d375 assn standard single material response packing

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight thru

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 59646 have indicated their part number contained asbestos prior to 1984; they continue to manufacturer the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt all ends

**Furnished Items And Quantity:**

1 handwheel

**Specification Or Standard:**

1 type and b class and 1 end and 3/4 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0