

View Online at <https://aerobasegroup.com/nsn/4820-00-274-7392>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Maximum Operating Temp:**

406.0 degrees fahrenheit single response

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

300.0 pounds per square inch 2nd response

**Thread Size:**

1.250 inches all ends

**Special Features:**

Renewable composition disc

**Material:**

Plastic tetrafluoroethylene flow control device

**Material Specification:**

Astm b-62 assn standard single material response seat

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight thru

**Supplementary Features:**

4this item has been reviewed for asbestos material. The current approved source, cage 59646, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Npt all ends

**Furnished Items And Quantity:**

1 handwheel

**Specification Or Standard:**

1 type and b class and 1rrjsz1-1/4 end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0