NSN 4820-00-275-2191

Globe Valve - Page 1 of 2

Flow Control Device:

Stem or disk



View Online at https://aerobasegroup.com/nsn/4820-00-275-2191

Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Threaded
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Features Provided:
Bonnet packing
Maximum Operating Pressure:
200.0 pounds per square inch 2nd response
Outside Diameter:
9.000 inches 1st end
Face To Face Distance:
11.500 inches
Thickness:
0.937 inches 1st end
Bolt Hole Diameter:
0.750 inches 1st end
Bolt Circle Diameter:
7.500 inches 1st end
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
6.187 inches 1st end
Material:
Iron cast body
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:

Straight through flanged ends

NSN 4820-00-275-2191

Globe Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0