

View Online at <https://aerobasegroup.com/nsn/4820-00-276-9021>

Thread Class:

2a all ends

Thread Direction:

Right-hand all ends

Offset Distance:

0.500 inches

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

275.0 degrees fahrenheit single response

Connection Style:

Flared (tube) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded external tube all ends

Mounting Facility:

Lug

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

16 all ends

Maximum Operating Pressure:

500.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Seat Angle:

45.0 degrees all ends

Outside Diameter Tube Accommodated:

0.500 inches all ends

Material:

Nickel alloy 400 stem or nickel alloy r-405 stem

Material Specification:

Qq-n-281 federal specification all material responses stem

Media For Which Designed:

Water-oil-gas 3rd response

Style Designator:

Straight through w/offset

Thread Series Designator:

Unf all ends

Furnished Items And Quantity:

2 nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0