

View Online at <https://aerobasegroup.com/nsn/4820-00-276-9029>

Flow Control Device:

Cone

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Union

Bolt Hole Quantity:

4 1st end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Mounting Position:

Horizontal or vertical

Features Provided:

Bonnet packing

Valve Size:

1.250 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

4.500 inches 1st end

Thickness:

0.438 inches 1st end

First Connection Face To Centerline Distance:

3.125 inches

Bolt Hole Diameter:

0.562 inches 1st end

Second Connection Face To Centerline Distance:

3.125 inches

Bolt Circle Diameter:

3.375 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

2.500 inches 1st end

Material:

Steel comp 410 stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by reply to pac aaql, and size 1 1/4 in.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A530b0