NSN 4820-00-276-9029

Stop-check Valve - Page 1 of 2

Flow Control Device:

Steel comp 410 stem



View Online at https://aerobasegroup.com/nsn/4820-00-276-9029

| Cone |
|--|
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Union |
| Bolt Hole Quantity: |
| 4 1st end |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Mounting Position: |
| Horizontal or vertical |
| Features Provided: |
| Bonnet packing |
| Valve Size: |
| 1.250 inches |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outside Diameter: |
| 4.500 inches 1st end |
| Thickness: |
| 0.438 inches 1st end |
| First Connection Face To Centerline Distance: |
| 3.125 inches |
| Bolt Hole Diameter: |
| 0.562 inches 1st end |
| Second Connection Face To Centerline Distance: |
| 3.125 inches |
| Bolt Circle Diameter: |
| 3.375 inches 1st end |
| Flange Face Design: |
| Raised straight 1st end |
| Raised Face Height: |
| 0.062 inches 1st end |
| Raised Face Diameter: |
| 2.500 inches 1st end |
| Material: |

NSN 4820-00-276-9029

Stop-check Valve - Page 2 of 2



| Media For Which Designed: |
|--|
| Steam single response |
| Style Designator: |
| Angle flanged ends |
| Reference Number Differentiating Characteristics: |
| As differentiated by reply to pac aaql, and size 1 $1/4$ in. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A530b0