NSN 4820-00-276-9030

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-276-9030

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Position:
Horizontal or vertical
Features Provided:
Bonnet packing
Valve Size:
1.500 inches
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.062 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.375 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.375 inches
Bolt Circle Diameter:
3.938 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.875 inches all ends

NSN 4820-00-276-9030

Stop-check Valve - Page 2 of 2

Material:

A530b0



Stainless steel stem
Media For Which Designed:
Steam single response
Style Designator:
Angle flanged ends
Reference Number Differentiating Characteristics:
As differentiated by type of bonnet, stop-check disk facility, and size and type of end connections
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: