## NSN 4820-00-276-9030

Stop-check Valve - Page 1 of 2

**Flow Control Device:** 

**Bonnet Type:** 

Disk

View Online at https://aerobasegroup.com/nsn/4820-00-276-9030



## Inside screw **Bonnet Attachment Method:** Bolted **Bolt Hole Quantity:** 6 all ends **Maximum Operating Temp:** 650.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal or vertical **Features Provided:** Bonnet packing Valve Size: 1.500 inches Maximum Operating Pressure: 150.0 pounds per square inch single response **Outside Diameter:** 5.062 inches all ends Thickness: 0.438 inches all ends **First Connection Face To Centerline Distance:** 3.375 inches **Bolt Hole Diameter:** 0.562 inches all ends **Second Connection Face To Centerline Distance:** 3.375 inches **Bolt Circle Diameter:** 3.938 inches all ends Flange Face Design: Raised straight all ends **Raised Face Height:** 0.062 inches all ends **Raised Face Diameter:** 2.875 inches all ends

## NSN 4820-00-276-9030

Stop-check Valve - Page 2 of 2



Material:

Stainless steel stem

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

**Reference Number Differentiating Characteristics:** 

As differentiated by type of bonnet, stop-check disk facility, and size and type of end connections

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0