NSN 4820-00-276-9032



Stop-check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-276-9032

Flow Control Device:
Cone
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Union
Bolt Hole Quantity:
4 all ends

Maximum Operating Temp:
650.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal or vertical

Features Provided:Bonnet packing

Valve Size:

0.750 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

3.812 inches all ends

Face To Face Distance:

5.250 inches

Thickness:

0.438 inches all ends

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

2.687 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.688 inches all ends

Material:

Steel seat

NSN 4820-00-276-9032

Stop-check Valve - Page 2 of 2



| Material | Specific | ation: |
|-----------------|----------|--------|
| | | |

Mil-e-22200 military specification single material response seat

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Reference Number Differentiating Characteristics:

As differentiated by reply to pac aaql, and size 3/4 in.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-e-22200 spec.