NSN 4820-00-276-9032

Stop-check Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-00-276-9032



Flow Control Device: Cone **Bonnet Type:** Outside screw-yoke **Bonnet Attachment Method:** Union **Bolt Hole Quantity:** 4 all ends Maximum Operating Temp: 650.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Mounting Position:** Horizontal or vertical **Features Provided:** Bonnet packing Valve Size: 0.750 inches Maximum Operating Pressure: 150.0 pounds per square inch single response **Outside Diameter:** 3.812 inches all ends Face To Face Distance: 5.250 inches Thickness: 0.438 inches all ends **Bolt Hole Diameter:** 0.562 inches all ends

Bolt Circle Diameter:

2.687 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.688 inches all ends

Material:

Steel seat

NSN 4820-00-276-9032

Stop-check Valve - Page 2 of 2



Material Specification:

Mil-e-22200 military specification single material response seat

Media For Which Designed:

Steam single response

Style Designator:

Straight through flanged ends

Reference Number Differentiating Characteristics:

As differentiated by reply to pac aaql, and size 3/4 in.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization: No Fiig: A530b0 Mil-std (military Standard):

Mil-e-22200 spec.