

View Online at <https://aerobasegroup.com/nsn/4820-00-277-1665>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

365.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

0.750 inches

**Maximum Operating Pressure:**

225.0 pounds per square inch 2nd response

**Outside Diameter:**

3.875 inches all ends

**Face To Face Distance:**

3.688 inches

**Thickness:**

0.375 inches all ends

**Bolt Hole Diameter:**

0.625 inches all ends

**Bolt Circle Diameter:**

2.750 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Plastic polytetrafluoroethylene packing

**Material Specification:**

Astm b62 assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight through flanged ends

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved sources, 53964, 14959, 82666, 55380, have indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0