NSN 4820-00-277-1666

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-277-1666

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
500.0 degrees fahrenheit 1st response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Bonnet packing
Valve Size:
1.000 inches
Maximum Operating Pressure:
225.0 pounds per square inch 2nd response
Outside Diameter:
4.500 inches all ends
Face To Face Distance:
4.188 inches
Thickness:
0.375 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Plain all ends
Material:
Copper alloy 922 seat
Material Specification:
Qq-c-390, aloy d4 federal specification single material response body
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Straight through flanged ends

NSN 4820-00-277-1666

Globe Valve - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0