## NSN 4820-00-283-1176

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-283-1176

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flareless 2nd end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 2nd end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Stainless steel flow control device
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Passivate
Style Designator:
Straight thru
Thread Series Designator:
Unjf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

## NSN 4820-00-283-1176

Restrictor Check Valve - Page 2 of 2

Fiig: A530b0

