

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2014>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

650.0 degrees fahrenheit 2nd response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

400.0 pounds per square inch 2nd response

Outside Diameter:

5.938 inches all ends

Thickness:

0.688 inches all ends

First Connection Face To Centerline Distance:

5.125 inches

Bolt Hole Diameter:

0.688 inches all ends

Second Connection Face To Centerline Distance:

5.125 inches

Bolt Circle Diameter:

4.625 inches all ends

Flange Face Design:

Plain all ends

Material:

Steel uns j03008 body

Material Specification:

Mil-s-853, class 6, type e military specification single material response stem

Media For Which Designed:

Hydraulic fluid, phosphate-ester base 2nd response

Style Designator:

Angle flanged ends

Reference Number Differentiating Characteristics:

As differentiated by pac name and 1 1/2 inch valve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

spec.