

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2046>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

6 all ends

Maximum Operating Temp:

425.0 degrees fahrenheit 2nd response

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

2.500 inches

Maximum Operating Pressure:

100.0 pounds per square inch 2nd response

Outside Diameter:

6.125 inches all ends

Face To Face Distance:

9.000 inches

Thickness:

0.500 inches all ends

Bolt Hole Diameter:

0.562 inches all ends

Bolt Circle Diameter:

5.000 inches all ends

Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

Media For Which Designed:

Water-oil-gas 1st response

Style Designator:

Straight through flanged ends

Test Data Document:

03950-cid88205t166 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0