NSN 4820-00-287-2640

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-2640

Pipe Size Accommodated:
1.500 inches 2nd end
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
50.0 gallons per minute
Maximum Operating Temp:
366.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+16.0/+30.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
1.500 inches all ends
Material:
Steel stem
Material Specification:
Qq-c-390 federal specification single material response stem
Media For Which Designed:
Water, fresh 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a

NSN 4820-00-287-2640

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0