

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2768>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

406.0 degrees fahrenheit 1st response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

11-1/2 all ends

Maximum Operating Pressure:

200.0 pounds per square inch 2nd response

Thread Size:

2.000 inches 1st end

Material:

Plastic polytetrafluoroethylene packing

Material Specification:

Astm b-62 assn standard single material response seat

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Angle

Supplementary Features:

This item has been reviewed for asbestos material. The current approved source, 12168, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

Test Data Document:

81348-ww-v-51 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Specification Or Standard:

2 type and a class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0