

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2768>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Threaded

**Maximum Operating Temp:**

406.0 degrees fahrenheit 1st response

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Thready Qty Per Inch (tpi):**

11-1/2 all ends

**Maximum Operating Pressure:**

200.0 pounds per square inch 2nd response

**Thread Size:**

2.000 inches 1st end

**Material:**

Plastic polytetrafluoroethylene packing

**Material Specification:**

Astm b-62 assn standard single material response seat

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Angle

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 12168, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Test Data Document:**

81348-ww-v-51 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Npt all ends

**Specification Or Standard:**

2 type and a class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0