

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2801>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

550.0 degrees fahrenheit 1st response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

400.0 pounds per square inch 2nd response

Thread Size:

0.375 inches all ends

Material:

Plastic polytetrafluoroethylene packing

Material Specification:

Astm b61 assn standard single material response body

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight thru

Supplementary Features:

This item has been reviewed for asbestos material; the current approved sources; 37239, 03268 and 76364 have indicated their part number contained asbestos material prior to 1984; they continue to manufacture the same part number without asbestos after 1984

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0