

View Online at <https://aerobasegroup.com/nsn/4820-00-287-2801>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Union

**Renewable Seat Ring Type:**

Threaded

**Maximum Operating Temp:**

550.0 degrees fahrenheit 1st response

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Thready Qty Per Inch (tpi):**

18 1st end

**Maximum Operating Pressure:**

400.0 pounds per square inch 2nd response

**Thread Size:**

0.375 inches all ends

**Material:**

Plastic polytetrafluoroethylene packing

**Material Specification:**

Astm b61 assn standard single material response body

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight thru

**Supplementary Features:**

This item has been reviewed for asbestos material; the current approved sources; 37239, 03268 and 76364 have indicated their part number contained asbestos material prior to 1984; they continue to manufacture the same part number without asbestos after 1984

**Thread Series Designator:**

Npt all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0