NSN 4820-00-287-2972

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-287-2972

Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
388.0 degrees fahrenheit 1st response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+71.0/+100.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Material:
Copper alloy
Media For Which Designed:
Oil, lubricating, diester base 1st response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-287-2972

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0